

# WinMax Global Enterprise Ltd.

Tel: +86 757 81811611 Fax: +86 757 81811621

E-mail: Sales@working-machinery.com Website: www.working-machinery.com

7th floor, East Building, No.13, Dade Road., Nanhai, Foshan 52825, Guangdong, China



• Control panel with electronic control of the blade raising and tilting



• Carriage moving on bearings



• 3 blade speed rotations with external leds to indicate the speed in use



• Scoring unit with independent motor



• Easy external adjustment of the scoring unit



• Carriage locking in every position



• System for inclined cuts



• Ripping fence with digital read-out



• Overhead guard with automatic rise and fall

# WinMax Global Enterprise Ltd.

Tel: +86 757 81811611 Fax: +86 757 81811621

E-mail: Sales@working-machinery.com Website: www.working-machinery.com

7th floor, East Building, No.13, Dade Road., Nanhai, Foshan 52825, Guangdong, China

## TECHNICAL DATA

BLADE	
Diameter	400 mm
Shaft diameter	30 mm
Speed rotation	3000 - 4000 - 5000 Rpm
Motor power	5,5 Kw
Tilting	0° - 45°

SCORING UNIT	
Diameter	120 mm
Shaft diameter	20 mm
Speed rotation	8500 Rpm
Motor power	0,75 Kw

MACHINE	
Maximum cutting length	3200 mm
Maximum cutting capacity between fence and blade	1300 mm
Maximum cutting height	120 mm
Fix table dimension	900 x 700 mm
Right support table dimension	640 x 500 mm
Back support table dimension	840 x 600 mm
Ø dust extraction outlet	120 mm
Air requirement with dust extraction at 20 m/s	1100 m <sup>3</sup> /h
Net weight	1100 Kg
Overall dimensions	3400 x 3300 x 1000 mm

**Max Wu**

**WinMax Global Enterprise Ltd.**

**Taiwan & China**

**Tel: +86 757 81811612**

**Fax: +86 757 81811621**

**Skype: winmax-davish**

**E-mail: sales@working-machinery.com**

**Website: www.working-machinery**