


Panelsaw TY2800 plus / TY3200 plus / TY3800 plus



Saw Guard_Type A(Optional)




Saw Guard_Type R(Optional)



Digital Readout on Rip Fence(Optional)



Digital Readout on Crosscut fence(Optional)



Hold-down Device(Optional)

Main technical parameter

Dimension of sliding table	2800*370/3200*370/3800*370mm
Gross cut capacity	3200mm
Width of cut between saw blade and rip fence	1250mm
Saw blade diameter	300mm (\varnothing 250- \varnothing 400)
Height of cut \varnothing 300mm	90mm
Diameter of guide shaft spindle	\varnothing 50mm
Height of cut with saw blade 300mm at 45°	60mm
Speed of main saw spindle	4000/6000rpm
Main spindle diameter	30mm
Tilting saw blade	0-45°
Main motor	4/5.5kw
Scoring saw blade diameter	120mm
Speed of scoring saw blade	9000r/min
Scoring spindle diameter	20mm
Scoring motor	0.75kw
Net weight	760kg
Gross weight (with wooden package)	870kg
Overall dimensions	3250 × 3150 × 900mm

(Super version)

Guide shaft spindle: \varnothing 50
Full size addition table
Lubrication pump
Support feeding frame
2 nd generation front control panel hood
Type-R protection hood
Advanced LED readout
Main motor 5.5KW
Scoring motor 0.75KW
Steel Pressure kit
Manual tilting 45°



WinMax Global Enterprise Ltd.

Tel:+86-757-81811612 Fax:+86-757-81811621

E-mail:sales@working-machinery.com Website:www.working-machinery.com

7th Floor, East Building, No.13, Dade Road, Nanhai, Foshan City, Guangdong Province, China