

Panelsaw TZ1600



Apply to processing all kinds of density boards, shaving boards, wood-based panels, ABS panels, PVC panels, organic glass plates and solid wood

Moveable table to guide track is plating chromium steel balls structure, exact and durable

Made of high-strength extruded aluminum alloy, movable table is high in strength and won't bend

With oxidation treatment, movable table surface is beautiful and hardwearing

Tilting angles of main and scoring saw blades are displayed directly by precision inclinometer

Specification / Model	TZ1600
Sliding table dimension (mm)	1600 x 360
Max. main saw blade dia. (mm)	300
Main saw bore (mm)	30
Max. cutting height with blade at 90° (mm)	80
Max. cutting height with blade at 45° (mm)	55
Main motor power (HP)	4
Main blade speed (RPM)	4000 / 6000
Scoring blade dia. (mm)	120
Scoring blade bore dia. (mm)	20
Scoring motor power (HP)	1
Scoring blade speed (RPM)	8000
Cutting width (mm)	1250
Cutting width adjustment	Manual Adjustment
Main blade tilting adjustment	Manual Adjustment
Main blade height adjustment	Manual Adjustment
Scoring blade height adjustment	Manual Adjustment
Scoring +/- direction adjustment	Manual Adjustment
Standard Equipments	Simple Sawblade Guard with Hose 1pc of 300mm Main Sawblade 1pc of 120mm Scoring Sawblade Miter Fence, Hold Down Device, Edge Shoe Inclinometer for Tilting Angle of Main Sawblade/Scoring Blade

WinMax Global Enterprise Ltd.

Tel:+86-757-81811612 Fax:+86-757-81811621

E-mail:sales@working-machinery.com Website:www.working-machinery.com

7th Floor, East Building, No.13, Dade Road, Nanhai, Foshan City, Guangdong Province, China